

BURNERS, COMBUSTION AND HEAT TRANSFER

(627) - (*) - EXPERIMENTAL INVESTIGATION OF SINGLE WOOD PARTICLE COMBUSTION IN AIR AND DIFFERENT O₂/CO₂/H₂O ATMOSPHERES

Alexander Mack (Germany)¹

1 - Institute of combustion and power plant technology, University of Stuttgart

Draft Paper

To achieve the objective of limiting global warming to below 2 °C compared to pre industrial times it is not sufficient to only decrease anthropogenic CO₂ emissions but the gas has to be actively removed from the atmosphere. In generating net negative CO₂ emissions it is also possible to balance residual emissions that are difficult to avoid for e.g. from the transportation sector. One possibility to achieve net negative CO₂ emission is bioenergy with carbon capture and storage (BECCS). On the other hand separated CO₂ from biomass conversion processes can be used to e.g. produce CO₂ neutral chemicals like methane or methanol. Oxyfuel combustion of biogenic fuels to generate a flue gas with high CO₂ concentration is a technology to efficiently separate CO₂ for storage or utilization. The Oxyfuel process describes the combustion of a given fuel with pure oxygen instead of air. To control the temperatures the oxygen is mixed with recycled flue gas containing mostly CO₂ and H₂O. Due to the different physical and chemical properties of the three atomic gases CO₂ and H₂O compared to N₂ the combustion behavior of the fuel is different under oxyfuel conditions compared to air combustion. Since grate incineration facilities are predestined for the combustion of solid biogenic fuels due to the relatively low requirements for fuel preparation and handling the oxyfuel process is investigated for solid biomass combustion in grate incineration furnaces. To better understand the combustion behavior of woody biomass under oxyfuel conditions relevant for grate incineration facilities single particle combustion experiments have been performed with varying O₂ concentrations (10 – 40 Vol.-%) in O₂/CO₂, O₂/CO₂/H₂O and O₂/H₂O atmospheres at 900 °C. The duration of the characteristic stages of the thermal conversion process ignition delay, volatile and char combustion has been investigated by means of taking videos with distinct frame rate. Additionally the temperature of the flame as well as the particle has been measured throughout the combustion process. The ignition delay has been evaluated according to the measured temperature profiles. It has been found that with increasing oxygen content the ignitions delay decreases. H₂O in the atmosphere further enhances this trend. The duration of the volatile combustion is influenced relatively little by the oxygen and H₂O content in the atmosphere. The temperature of the flame on the other hand is increasing with higher oxygen concentration. Char combustion duration is decreasing with increasing oxygen content and at a given O₂ concentration additional H₂O in the atmosphere decreases the char combustion duration. The particle temperature during char combustion is lower in the oxyfuel cases compared to air combustion however H₂O increases the temperature. One can conclude that considering the carbon consumption endothermic gasification reactions of C with CO₂ and H₂O gain in relevance during oxyfuel combustion so that the particle temperature is lower compared to air operation. Also substitution of CO₂ by H₂O in the atmosphere at the same O₂ concentration leads to decreased char combustion durations.

Palavras-chave : Oxyfuel, Oxy steam, Biomass combustion, single particle